

FlashBus Spectrim Lite Dual & Quad

Bus-Mastering frame grabber for cost sensitive applications

Integral Technologies' OEM Solutions Group introduces the FlashBus Spectrim Dual and Quad capture cards capable of simultaneous streaming capture from two or four composite input sources. Both of these boards use the same software and drivers and can be used with applications previously developed for any board in the FlashBus Spectrim family.



Key Features

- ◆ Bus-mastering video acquisition
- ◆ Philips TriMedia™ Video Processor
- ◆ Real-time transfer of video to system or display memory
- ◆ 16 MB SDRAM frame buffer
- ◆ High-quality video scaling to arbitrarily sized windows
- ◆ Simultaneous preview/capture from up to 4 composite inputs
- ◆ CCIR and square pixel capture resolution
- ◆ NTSC and PAL video formats
- ◆ Area of interest transfers to/from system and on-board memory
- ◆ Real-time image flip, rotate, and mirror
- ◆ Windows 98, ME, 2000, 2003, XP, Vista and Linux drivers
- ◆ Windows-based FBG video capture application
- ◆ Optional SDK with sample applications
- ◆ Graphical overlay and alpha blending support

Applications

- ◆ Image analysis
- ◆ Scientific imaging
- ◆ Microscopy
- ◆ Law enforcement
- ◆ Video surveillance
- ◆ Traffic control
- ◆ Medical imaging

FlashBus Spectrim Lite Dual & Quad

OEM Highlights

Bus-Mastering Performance

FlashBus Spectrim's high speed bus-mastering capability delivers real-time video data to system or display memory, without intervention from the host CPU.

TriMedia™ Video Processor

Equipped with the Philips TriMedia Video processor and a 16 mb SDRAM frame buffer the Flashbus provides smooth interpolated scaling, hardware overlay, and real-time video rotation.

High-Quality Video Capture

FlashBus Spectrim provides high-quality capture from up to four composite video sources simultaneously in NTSC or PAL format. Video can be captured and stored in either square pixel or CCIR-601 resolutions, and can be scaled to any arbitrary size.

Software Developers Kit

As with all Integral Technologies' frame grabber products, a comprehensive software developers kit is available that provides access to the features of the FlashBus Spectrim Lite hardware. The SDK includes DLLs for Microsoft Windows 9x, ME, 2000, 2003, XP, Vista and Linux operating systems. Source code samples are included in both C and Visual BASIC to provide insight to various hardware functions of FlashBus Spectrim Lite.

Integral Technologies provides free technical support to developers using the FlashBus Spectrim SDK.

Specifications

BUS FORMAT

- ◆ PCI 2.2 compliant
- ◆ Universal PCI connector

VIDEO INPUTS

- ◆ 4 Composite inputs
- ◆ BNC connectors

VIDEO DIGITIZATION

- ◆ NTSC M, NTSC N, NTSC 4.43, NTSC-Japan,
- ◆ SECAM, PAL BGDHI, PAL N, and PAL M format support
- ◆ ITU-601 digitization
- ◆ Software programmable control of offset, gain, hue, and saturation
- ◆ EEPROM for storing configuration and calibration settings

VIDEO ACQUISITION

- ◆ Philips TriMedia video processor
- ◆ Smooth interpolated scaling to randomly sized windows
- ◆ Bus-mastering video transfers to system or display memory
- ◆ Hardware overlay of graphics over video
- ◆ RGB 32/24/16/15/8 and YUV 4:2:2 pixel formats
- ◆ Area of interest transfers to and from on-board and system memory
- ◆ 16 MB SDRAM frame buffer
- ◆ Real-time image flip, mirror, or rotate

SOFTWARE DEVELOPERS KIT

- ◆ Windows 98, ME, 2000, 2003, XP Vista and Linux DLLs
- ◆ Video for Windows drivers
- ◆ Direct Show support
- ◆ Visual Basic support
- ◆ TWAIN support
- ◆ MCI support
- ◆ Sample application source code
- ◆ Video for Linux 2 support

VIDEO CABLES

- ◆ Composite, S-Video, and trigger cables available
- ◆ Custom cables and connector pinouts available upon request

ORDERING INFORMATION

- ◆ FlashBus Spectrim SDK: #3430
- ◆ FlashBus Spectrim Quad: #3044
- ◆ FlashBus Spectrim Dual: #3041